



TECHNICAL PRODUCT DATASHEET

CHEMICAL PROTECTION







UPDATED: 07/06/2024

GRIPPAZ 306/BL

Heavyweight, 6Mil thick, extended cuf (30cm) Nitrile Semi-Disposable, Powderfree, Patented Fishscale Grip

The Grippaz 306 extended cuff 30cm long nitrile semi-disposable range revolutionised the nitrile glove market by intertwining a premium 6mil 100% NBR base with an ambidextrous worldwide patented fish scale grip pattern. When tested at Satra, the fish scale grip pattern provided 3x the grip compared to the leading nitrile disposables and 30% better grip compared to a diamond grip pattern.

The extended cuff, heavyweight design has been specifcally designed with the food, chemical & pharmaceutical industry in mind, where maximum grip and dextertity is required when working with harsher

This product is especially popular in the food industry above both a regular single-use nitrile disposable and the more traditional latex rubber or nitrile gauntlets. The increased puncture and tear resistance reduces down time through glove breakages. Semi-reusable and can be used over high cut resistant liners or even chainmail in slaughterhouses or butchery.



FEATURES AND TECHNOLOGY







OIL REPELLENT



SUPERIOR



SCALE



NITRILE

DISPOSABLE



















RAILWAYS AGRICULTURE JANITORIAL

TECHNICAL INFORMATION

ORDER REF#	G/DG-GRPZ-306
COATING MATERIAL	N/A
PACKING	PER PACK: 1 x Box of 50
	PER CASE: 10 x Box of 50
SIZES AVAILABLE	S, M, L, XL, 2XL
EU TYPE CERTIFICATION BY	SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland (Notified Body No. 2777)



EN ISO 374-1 :2016 / TYPE B

X' denotes not tested.
 Where applicable, EN388:2016 scores take precedent and are ongoing.
 There is no correlation between coupe test levels and EN ISO 13997 /
TDM cut test levels.



Protection against viruses - PASS











Fax: +44 (0)1902 451 271











TECHNICAL PRODUCT DATASHEET

CHEMICAL PROTECTION







UPDATED: 07/06/2024

CERTIFICATION LEGENDS





* For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

EN ISO 374-1 :2016 / TYPE



A Methanol

B Acetone

Acetone
Acetonitrile
Dichloromethane
Carbon Disulphide

F TolueneG DiethylamineH Tetrahydrofuran

Ethyl Acetate

EN ISO 374-5:2016



TYPE A - Gloves have achieved level 2 or greater against six of the chemicals listed in EN ISO 374-1 (below). The tested chemicals are identified by their code letters under the flask pictogram.

TYPE B - Achieved level 2 or greater against at least three of the chemicals .

TYPE C - Achieved at least a level 1 against one of the chemicals.

J	n-Heptane
K	Sodium Hydroxide (40%)
L	Sulphuric Acid (96%)
M	Nitric Acid (65%)
N	Acetic Acid (99%)
0	Ammonium Hydroxide (25%)
Р	Hydrogen Peroxide (30%)
S	Hydrofluoric Acid (40%)
т	Formaldehyde (37%)

EN407:2020



Limited Flame Spread (0-4)

Contact Heat (0-4)

Convective Heat (0-4)

Radiant Heat (0-4)

Small Splashes Molten Metal (0-4)

Larce Quantity Molten Metal (0-4)

EN511:2006





* For details regarding maximum permissable user exposure, see seperate sheet.

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Gloves should not be used when there is a risk of entanglement with moving machine parts. 2. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 3. The gloves should not come in contact with a naked flame or fire. 4. Do not subject to high speed or serrated blades. 5. Always read enclosed user instructions before using these gloves. 6. When used, protective gloves may provide less resistance to the dangerous chemicals due to changes in physical properties. 7. Movements, snagging, rubbing, de-gradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

FOOD TEST INFORMATION


Details of the suitability for contact with various food categories as detailed in EEC Directive are available on request. Please quote product reference when enquiring.



For more information about this product, or to access the Declaration of Conformity or Product Certification, visit; https://www.ultimateindustrial.co.uk/hand-and-arm/grippaz-306-bl/

If appropriate to the product, EC/EU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCi customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCi are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCi assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademsks*" or registered® trademsks of their respective holders. Ou CLI Limited, 2025 UCI Limited,





📵 **Fax:** +44 (0)1902 451 271



Web: www.ultimateindustrial.co.uk



¹ Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² 'X' denotes Not Tested. ³ Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.